

BJB///OEM-Line

32.130.0008

Linear Flat System



Emb.	Peso	Referencia
12	200 g	32.130.0008.00

Linear Flat - flat LED module
Exchangeable LED-lamp - No additional tools required

Height (build in):	15 mm
Width:	37,09 mm
Length:	1168 mm
Colour temperatur:	4000 K
CRI:	>80
Power consumption:	34.2 W
Typical operating voltage:	ca. 47 V
Rated current:	700 mA
Flux at Tc 25° C:	4209 lm
Module efficiency at Tc 25° C:	123 lm/W

- Quick and easy installation even in very narrow luminaires (slot light channels)
- Audible and tactile feedback during mounting process „Click-Fit“
- Straight and pure design, genuine high grade materials
- Tight colour tolerance: McAdams 3.5 SDCM
- Beam angle: 120°
- Life span L70 > 50.000 h
- Ambient temperature: -30 °C bis + 45 °C
- Module efficiency and Luminous flux measured at Tc = 25 °C
- TC: max. 65° C
- Risk group: 0
- Protection class: IP20
- Guarantee*: 5 years
- Approval marks: RoHs
- Tolerances of optical and electrical data: +/- 10%'
- Warranty conditions of BJB GmbH & Co. KG as stated on page 100 of the LED Applications catalogue (Issue No.1 - 2014) and as available via the Internet under www.bjb.com/warranty-conditions.html are valid.

LED

