

Sommario

	Page Pagina
JOLLY SLIM HV 32 - 1...10 V & PUSH	184-185
MAXI JOLLY SLIM 60 - 1...10 V & PUSH	186-187
MAXI JOLLY SLIM DALI 60	188-189
MAXI JOLLY SLIM HV 60 - 1...10 V & PUSH	190-191
MAXI JOLLY SLIM HV DALI 60	192-193
MAXI JOLLY SLIM DALI 60 LS - LEDset2	194-195
T-LED 80/350 1...10V SLIM	196-197
T-LED 80/500 1...10V SLIM	198-199
T-LED 80/700 1...10V SLIM	200-201
T-LED 80/350 DALI SLIM	202-203
T-LED 80/500 DALI SLIM	204-205
T-LED 80/700 DALI SLIM	206-207
T-LED 90/580 DALI SLIM	208-209
T-LED 80/500 DALI SLIM LS - LEDset2	210-211

4. STREET LIGHTING AND ENERGY SAVING LED DRIVERS - ALIMENTATORI LED PER ILLUMINAZIONE STRADALE E A RISPARMIO ENERGETICO **212-267**

Direct current dimmable electronic drivers with DIP-SWITCH
Alimentatori elettronici regolabili in corrente continua con DIP-SWITCH

4.1 STREET LIGHTING SERIES - SERIE PER ILLUMINAZIONE STRADALE

SIRIO 150/200-700	214-215
SIRIO 150/300-1050	216-217
SIRIO 150/700 ST2	218
SIRIO 150/1050 ST2	219
SIRIO 100 - 1...10 V & BILEVEL	220-221
SIRIO 120/600-2100 - 1...10 V & BILEVEL	222-223
SIRIO 150/200-700 - 1...10 V & BILEVEL	224-225
SIRIO 150/300-1050 - 1...10 V & BILEVEL	226-227
MAXI JOLLY US FP - FULL PROGRAMMABLE	228-229
SIRIO 100/200-700 FP - FULL PROGRAMMABLE	230-231
SIRIO 150/200-700 FP - FULL PROGRAMMABLE	232-233
SIRIO 150/300-1050 FP - FULL PROGRAMMABLE	234-235
POLARIS 150/200-700 FP - FULL PROGRAMMABLE	236-237