

Sommario

| | Page Pagina |
|---------------------------------|----------------|
| LS | 271 |
| EFU | 272 |
| EFUR 1...10 V | 273 |
| WU RGB IR & PUSH | 274-275 |
| VST BI | 276-277 |
| VST | 278-279 |
| VST II | 280-281 |
| VSTR RGB - 1...10 V / PUSH / IR | 282-283 |

5.2 LINEAR CASE - LINEARI

| | |
|------------------------------|---------|
| DC 60W 24V DALI SLIM | 284-285 |
| DC 60W 24V SLIM | 286 |
| DC 60W 24V SLIM R - 1...10 V | 287 |

6. IP RATED LED DRIVERS - ALIMENTATORI LED PROTETTI IP

Direct current electronic drivers
Alimentatori elettronici in corrente continua

288-297

| | |
|--------------|---------|
| DCC/U S IP54 | 290-291 |
| STCP/U IP54 | 292 |
| SMTP/U IP54 | 293 |
| SLIM/U IP65 | 294 |
| DC SL/U IP65 | 295 |
| ST2 IP67 | 296 |
| DC T-TU IP68 | 297 |

7. LOW VOLTAGE LED DRIVERS - ALIMENTATORI LED IN CORRENTE CONTINUA A BASSA TENSIONE

Direct current electronic drivers
Alimentatori elettronici in corrente continua

298-305

| | |
|------------------------|---------|
| LV HR | 300 |
| LV MICRO Z | 301 |
| LV RGB 250 / 350 / 500 | 302-303 |
| LV RGB IR | 304-305 |