

## SYMBOLS - SIMBOLOGIA



### PROTECTIONS AGAINST DISCHARGES AND HIGH VOLTAGE SPIKES

Controlgear equipped with protections against discharges and high voltage spikes on the mains.



### AUXILIARY OUTPUT

Controlgear equipped with 12 V auxiliary output.



### SYNCHRONISATION

Controlgear equipped with synchronisation terminal block (see page). Compliance with EN 60929.

34C/1130/DC 15.4c: Other manufacturer's protocols operated with ELV where the owner of the system specifies the type of insulation used in the system technical documentation.



### NTC

Controlgear equipped with input for external thermal sensor (not supplied).



### LOOPING

Component or equipment suitable for cascade connection.



### COOKER HOOD

Controlgear suitable for house hold and similar electrical appliances (cooker hoods).



### SLOT FIX

The controlgear can be secured with slot for screws.



### HOLE CEILING

Hole diameter for ceiling.



The EL symbol is used for "electronic" in the following applications:

- a.c. maintained emergency electronic controlgear.
- a.c./d.c. maintained emergency electronic controlgear.
- d.c. maintained emergency electronic controlgear.



### PROTECTIONS

Controlgear equipped with protections.



### PROTEZIONE SCARICHE E PICCHI DI TENSIONE

Alimentatore provvisto di protezione contro scariche e picchi di tensione sull'ingresso.



### USCITA AUSILIARIA

Alimentatore provvisto di uscita ausiliaria a 12 V.



### SINCRONISMO

Alimentatore sincronizzabile con altri dispositivi (vedi pagina). Conformità alla EN 60929.

34C / 1130 / DC 15.4c: Altri protocolli produttore azionati con ELV in cui il proprietario del sistema specifica il tipo di isolamento utilizzato per quel sistema nella documentazione tecnica del sistema stesso.



### NTC

Alimentatore provvisto di ingresso per sensore di temperatura esterno (non fornito).



### LOOPING

Alimentatore provvisto di morsetti raddoppiati sull'ingresso per connettere in cascata con altri dispositivi.



### COOKER HOOD

Alimentatore adatto per essere impiegato in apparecchi elettrici d'uso domestico e similare (cappe).



### FISSAGGIO

Alimentatore provvisto di asole di fissaggio.



### DIAMETRO FORO CONTROSOFFITTI

Misura foro per incasso per controsoffitti.



Il simbolo EL è utilizzato per indicare "elettronico" nelle seguenti applicazioni:

- alimentatore elettronico d'emergenza permanente in c.a.
- alimentatore elettronico d'emergenza permanente in a.c./d.c.
- alimentatore elettronico d'emergenza permanente in d.c.



### PROTEZIONI

Alimentatore provvisto di protezioni.