



Made in Europe

**Rated Current  
Corrente Nominale**

150 mA  
200 mA  
250 mA

**Power  
Potenza**

5 W  
7 W  
8,7 W

**Reference Norms****Norme di riferimento:**

EN 55015  
EN 61347-1  
EN 61547  
EN 62031  
EN 62471

**LED color  
Colore LED**

3000 K  
4000 K

Article Articolo	Code Codice	Temp. Color Colore	Typ Current (I typ) mA	Flux Im <sup>(1)</sup> (I typ 25°C) tc	Flux Im <sup>(1)</sup> (I typ 80°C) tc	V	Power (W)	ta °C	tc °C	CRI	Beam angle
LED SPOT 600	128062/830/20	3000K	150	580	520	33,8	5	-20...+45	90	>80	20
			200	710	640	34,3	7	-20...+45			
			250	900	810	34,8	8,7	-20...+35			
LED SPOT 600	128062/830/35	3000K	150	580	520	33,8	5	-20...+45	90	>80	35
			200	710	640	34,3	7	-20...+45			
			250	900	810	34,8	8,7	-20...+35			
LED SPOT 600	128062/830/55	3000K	150	580	520	33,8	5	-20...+45	90	>80	55
			200	710	640	34,3	7	-20...+45			
			250	900	810	34,8	8,7	-20...+35			
LED SPOT 600	128062/840/20	4000K	150	615	550	33,8	5	-20...+45	90	>80	20
			200	750	670	34,3	7	-20...+45			
			250	960	860	34,8	8,7	-20...+35			
LED SPOT 600	128062/840/35	4000K	150	615	550	33,8	5	-20...+45	90	>80	35
			200	750	670	34,3	7	-20...+45			
			250	960	860	34,8	8,7	-20...+35			
LED SPOT 600	128062/840/55	4000K	150	615	550	33,8	5	-20...+45	90	>80	55
			200	750	670	34,3	7	-20...+45			
			250	960	860	34,8	8,7	-20...+35			

<sup>(1)</sup> The mentioned data can have a 10% tolerance - Il dato indicato può avere una tolleranza del 10%.

- SPOT LED module for built-in use.
  - Polycarbonate spotlight 50mm diameter.
  - PMMA diffusing or transparent lens to cover the spotlight.
  - High efficiency of the system in combination with TCI drivers.
  - Color tolerance within 3 MacAdam.
  - Perfect light uniformity.
  - Anodized aluminium heat sink.
  - Provided with power wires and tear-proof cable clamps.
  - Lifetime 50.000h L 70.
  - Emission angle 20°/35°/55°.
  - The use is guaranteed in combination with TCI drivers only.
- For photometric test report and further information please see our web site [www.tci.it](http://www.tci.it) or contact our technical department.

- Modulo SPOT LED da incorporare.
  - Riflettore in policarbonato diametro 50 mm.
  - Lente diffondente o trasparente in PMMA a copertura del riflettore.
  - Alta efficienza del sistema in combinazione con driver TCI.
  - Tolleranza di colore 3 step MacAdam.
  - Perfetta uniformità di luce.
  - Dissipatore in alluminio anodizzato
  - Fornito con cavi di alimentazione e fissacavo antistrappo.
  - Lifetime 50.000h L 70.
  - Angolo di emissione 20°/35°/55°.
  - L'utilizzo è garantito in combinazione con driver TCI.
- Per test fotometrici e ulteriori informazioni consultare il nostro sito internet [www.tci.it](http://www.tci.it) o contattare il nostro ufficio tecnico.

